Woodland Haze





Engineered Wood Flooring

Species:	European White Oak
Style:	Plank Flooring
Construction:	Multiply Engineered Wood
Base:	Carb 2 Eucalyptus Plywood
Length:	> 66% 86.6" < 33% Random 23.6" - 63.0"
Width:	9 1 / 2"
Thickness:	5 / 8" 4mm Sawn cut
Joint:	4-sides Tongue and Groove with micro-bevel
Surface:	Light Wire Brushed
Finish:	Germany Treffert AL ₂ O ₃ Anti-scratched UV Lacquer prefinished
Grade:	Light Character
Packing:	34.10 sqft / pack

Installation:

Glue down

🗹 Nailed

Floating on concrete

Floating on underlay

Plank



*Wood may oxidated in air so color could be little vary from batch to batch while watch by people's eye.

Woodland Haze







Specification



Real Wood Veneer

Sawn-cut veneer in species: White Oak from sustainable forests, with full chain of custody.

• Floor Base

CARB 2/EPA-compliant Dynea ACIC phenolic glue plywood base.

Coating System

Finished with Treffert aluminum oxide UV coating in a matte gloss, wire-brushed with natural grain texture.

Accurate Milling

Precise T&G with micro bevel, crafted with German Homag technology.

• Well Select Timber Grading

Sorted into Select Natural, Light Character, with unique beauty of timber.

Mouldings Avalable



T - modling 86.6" × 4/5" × 1/2"



Quarter Round 86.6" x 2/3" x 2/3"



Stair Nosing & Treads



Eco-friendly Floors for Greener Living



Lifetime Structural

25 Year Residentia



0 Year Commercial




Glue-Down Installation



Installation

Nail-Down Installation



Floating Installation

Fully compliant with NWFA standards.











Copying right 2024 All right reserved Lamont Timber Creations Inc.